



## DGWMX303C-1

1-Pump 、 Economic Type

### Main Function :

To cut/punch(all kinds of round/square/special holes and slot type)/chamfer/horizontal bending/vertical bending/ emboss/Press cable thread /twist/anti-press flat the copper/aluminum busbar ect.

### Function Introduction :

- 1.Cutting unit adopts double-column shear structure (patent number: ZL201120262802.1),Cut mouth flat, no burr, no waste.
- 2.Single arm type structure(patent number:ZL201120262917.1) which is a totally whole one,improving concentric degree of moulds,prolonging the service life of the moulds,saving time of change.
- 3.Bending unit adopts closed bending structure,making it is more uniform when processing horizontal bending and embossing. Also prolonging the service life.
- 4.Adopting PLC controlled,compared to the traditional relay,more stable and reliable.
- 5.Hydraulic tank with thick plate welding,and is treated by phosphating, making hydraulic oil can be long time used and will not degenerate.
- 6.The machine is with two types of common type and CNC type.

### The Paramter:

Item	DGWMX303C-1	DGWMX503C-1
Max. Punching Force (KN)	300	500
Punching Diameter Range (MM)	Φ4.3-25	Φ4.3-32
Max. Process Thickness (MM)	12×160	162×00
Max. Vertical Bending Width (MM)	120	120
Work Bench Size(MM)	1400×1000	1500×1200
Size Of The Machine (MM)	1500×1150×1170	1750×1350×1250
Weight Of The Machine(KG)	1170	1790
Bending Angle CNC	NO	NO
The Three Units Work At The Same Time	NO	NO

### Package With:

Cutting Unit	1 Set Of Scissor
Punching Unit	8 Sets Of Punching Molds
Bending Unit	2 Sets Of Vertical Bending Molds (3), 1 U Bending Molds, 2 Sets Of Horizontal Bending Molds(3), 1 Embossing Molds
Other	Foot Switches(3), Sealing Ring 1 Bag, Manual,Certification, Packing List (each is 1 set)



## SXC30-550/750

Deep Throat Punch Press

### Main Features:

- 1.This machine is mainly to punching press
- 2.Steel plate welded bed, stress annealing treatment after welding, to ensure the rack is not deformed after the long-term used.
- 3.PLC controlling, with digital axis system.Easy to carry out artificial positioning.The machine can be stopped at the time of unmanned operation.
- 5.High flow gear pump,processing with speed,Step speed can reach 12 times/min.

### The Paramter :

ITEM	SXC30-550	SXC30-750
Nominal Pressure	300KN	300KN
Max Processing Diameter	60MM	60MM
Max Processing Thickness	6MM	6MM
Throat Depth	550MM	750MM
Main Motor Power	5.5KW	5.5KW